

屋内消火栓 配管摩擦損失水頭 m/100m

管種 JIS G3452

流量 呼称	32mm	40mm	50mm	65mm	80mm	100mm	125mm	150mm
60L/min	4.756	2.258	0.701	0.208	0.044	0.025	0.009	0.004
70L/min	6.326	3.004	0.932	0.277	0.059	0.033	0.012	0.005
120L/min	7.146	8.141	2.526	0.749	0.160	0.088	0.031	0.001
130L/min	19.883	9.440	2.929	0.869	0.186	0.103	0.004	0.002
140L/min	22.805	10.828	3.360	0.997	0.213	0.118	0.004	0.018
150L/min	25.910	12.300	3.820	1.130	0.240	0.130	0.005	0.020
190L/min	40.122	19.050	5.911	1.753	0.375	0.206	0.007	0.031
260L/min	49.777	34.033	10.560	3.131	0.670	0.370	0.129	0.056
300L/min	93.400	44.350	13.760	4.080	0.870	0.480	0.170	0.070



西日本防災システム
NISHINIHON BOHSAI SYSTEM Co., Ltd
<http://www.nbs119.co.jp/>



弊社Top Pageへ 

屋内消火栓 配管摩擦損失水頭 m/100m

管種

JIS G3454
Sch40

流量 呼称	32mm	40mm	50mm	65mm	80mm	100mm	125mm	150mm
60L/min	4.888	2.367	0.714	0.240	0.105	0.028	0.010	0.004
70L/min	6.502	3.149	0.950	0.320	0.140	0.038	0.014	0.006
120L/min	17.622	8.533	2.573	0.866	0.379	0.102	0.036	0.015
130L/min	20.435	9.895	2.984	1.005	0.439	0.118	0.042	0.018
140L/min	23.437	11.350	3.423	1.153	0.504	0.136	0.048	0.021
150L/min	26.630	12.890	3.890	1.310	0.570	0.150	0.050	0.020
190L/min	41.235	19.968	6.021	2.027	0.886	0.238	0.084	0.036
260L/min	73.666	35.672	10.756	3.622	1.584	0.425	0.151	0.064
300L/min	95.990	46.480	14.020	4.720	2.060	0.550	0.200	0.080



西日本防災システム
NISHINIHON BOHSAI SYSTEM Co., Ltd
<http://www.nbs119.co.jp/>



弊社Top Pageへ 